

**ZUMTOBEL**

GLOBAL TRAC™

GLOBAL TRAC™ LUMINAIRE



Large Trackhead

ONICO

Large Trackhead for Global Trac™

- Passive cooling achieved by innovative thermal design
- Driver integrated into the housing
- Die-cast aluminum housing
- Rotatable head through 328° and tiltable through 90°
- Black polycarbonate front ring provides excellent glare control
- Front ring serves for accommodation of accessories
- Reflector of aluminized polycarbonate, highly specular, iridescence-free
- Specular reflector designed to be interchangeable



Suitable for Dry Locations

IBEW UNION MADE

DELIVERED LUMENS	COLOR TEMPERATURE	COLOR RENDERING	WATTS
2100 lm – 2751 lm	3000 K	CRI 80+	24 W
3100 lm – 4061 lm	3500 K	CRI 90+	36 W
	4000 K		
	(MacAdam 3 Step)		
	TGR ¹		

Trackhead Order Code

ONICL	2	3	4	5	6	UNV
1 FIXTURE	ONICL Spotlight					
2 OUTPUT	24W 1800 lm – 2358 lm 36W 3100 lm – 4061 lm					
3 LED MODULE	830 3000K, 80CRI 835 3500K, 80CRI 840 4000K, 80CRI TG TGR ¹ 930 3000K, 90CRI 935 3500K, 90CRI 940 4000K, 90CRI					
4 BEAM SPREAD	SP Spot 10° FL Flood 24° WF Wide Flood 38°					
5 FINISH	WH White BK Black					
6 ADAPTER	TEK 2-Circuit, 120V HTEK 2-Circuit, 277V					
7 DRIVER	UNV 120V/277V					

¹ Available only with 36 W*Accessories Order Code*


60700374	Interchangeable Spot Reflector	60700368	Soft Outline Lens
60700375	Interchangeable Flood Reflector	60700370	Oval Outline Lens
60700376	Interchangeable Wide Flood Reflector	60700372	Honeycomb Louver, Black

Track Order Code


Track elements must be ordered separately. Consult Global Trac™ specification sheets for order codes.

Light Distribution


36 W Spot: 10°



36 W Flood: 24°



36 W Wide Flood: 38°



Multipliers

CCT and CRI

CRI	CCT	Multiplier
90	3000	1.00
	3500	1.07
	4000	1.08
80	3000	1.27
	3500	1.30
	4000	1.31

Illuminance at a Distance | 36 W, 90 CRI, 3000 K

10° Spot

D	Center Beam FC	L	W
5'	2102	0.8'	0.8'
7.5'	934	1.3'	1.3'
10'	525	1.8'	1.8'
12.5'	336	2.3'	2.3'
15'	233	2.7'	2.7'

24° Flood

D	Center Beam FC	L	W
5'	561	2.1'	2.1'
7.5'	249	3.1'	3.1'
10'	140	4.1'	4.1'
12.5'	89	5.2'	5.2'
15'	62	6.2'	6.2'

38° Wide Flood

D	Center Beam FC	L	W
5'	290	3.0'	3.0'
7.5'	129	4.6'	4.6'
10'	72	6.1'	6.1'
12.5'	46	7.7'	7.7'
15'	32	9.2'	9.2'







CBCP: 52545 | Lumens: 3100
LPW: 86 lm/W

CBCP: 14047 | Lumens: 3100
LPW: 86 lm/W

CBCP: 7262 | Lumens: 3100
LPW: 86 lm/W

Dimensions



Technical Detail

1) Track: ONICO is compatible with Global Trac™.

2) Wattage & CCT: Unit is available in 24 W or 36 W, 3000 K, 3500 K, 4000 K and in 80+ CRI, 90+ CRI. True Gamut Rendering (TGR, 3000 K, 90CRI) is offered with 36 W only, enabling lively color effects particularly with white and colored apparel.

3) Dimming: Unit is only available with a non-dimmable universal 120/277V driver.

4) Beam Spread: Unit is available with Spot, Flood or Wide Flood beam spread.

5) Accessories: Honeycomb louver (black), oval outline lens, soft outline lens and interchangeable reflectors (Spot, Flood and Wide Flood distribution) are offered as accessories.

6) Housing: The housing is made of die-cast aluminum painted white.

7) Optic: The reflector is polycarbonate (PC) aluminum sputtered specular.

8) Life: 50,000 hours, L80.

9) Weight: 3.8 lbs.