

2.5" Pendant (shown) / Wall Mount



LENS OPTIC OPTIONS

SLOTLIGHT LED III

2.5" Individual Luminaires and Straight Runs

- Continuous line of light
- Available in a variety of lengths to suit any application
- Patented roll lens for seamless installation
- Rollable lens for all direct optics: opal flush / regressed (150' max length) and asymmetric (50' max length)
- Uniformly illuminated corners
- Available with occupancy and daylight sensors
- UGR <19 with LRO Lens

IBEW UNION MADE

PROGRAMMABLE LM/FT RANGES *

OPTIC	3000 K		3500 K		4000 K	
	MIN	MAX	MIN	MAX	MIN	MAX
Opal	342	933	351	956	354	965
LRO	274	748	281	766	284	773
Asymmetric	188	1026	192	1048	194	1059
Indirect Batwing	411	1120	421	1147	427	1155
Indirect Asymmetric	135	734	138	752	139	760

* Exact programming levels available as a modification.



Suitable for Damp and Wet Locations

Order Code

1	2	3	4	5	6	7	8	9	10	9	12	13	14	15	16	17	18	19
1 FIXTURE	SL3I Individual ¹ SL3R Run ²																	
2 WIDTH	2 2.5"																	
3 MOUNTING	PA Pendant 70" Feed PB Pendant 157" Feed WM Wall Mount																	
4 WHOLE LENGTH	XXXX Length in 1" Increments																	
5 FRACTIONAL LENGTH	N 0/8 A 1/8 B 2/8 C 3/8 D 4/8 E 5/8 F 6/8 G 7/8																	
6 DISTRIBUTION	D Direct Only I Indirect Only C Single Channel Direct/Indirect S Separate Switching Direct/Indirect																	
7 DIRECT OUTPUT	08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
8 DIRECT OPTIC	P Opal Flush (Roll Optic) L Luminance Reducing ³ A Asymmetric (Roll Optic) N None																	
9 INDIRECT OUTPUT	08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
10 INDIRECT OPTIC	B Batwing A Asymmetric N None																	
11 CRI	9 90 CRI																	
12 CCT	30 3000 K 35 3500 K 40 4000 K 00 Tunable White 2700–6500 K ⁴ ZS Zumtobel SPECTRUM ⁴																	
13 DRIVER	U 0-10 V, 1%, 120 V / 277 V D DALI, 1%, 120 V / 277 V H Lutron EcoSystem, 1%, 120 V / 277 V C 0-10 V, 1%, 347 V T Tunable White DALI Signal																	
14 FINISH	W White S Silver B Black																	
15 CONTROL OPTIONS	N None E Enlighted ⁵ W Wireless ⁶																	
16 ACCESSORIES *	C EM Circuit ⁷ B Battery ⁸																	
17 EM START	1 Start EM 0 None																	
18 EM MID	X Quantity from 1 to 9 0 None																	
19 EM END	1 End EM 0 None																	

* COMPLETE 16-19 IF EMERGENCY OPTIONS ARE REQUIRED

- Must be between 24" and 96" in length. Individual fixtures will be provided with roll optic installed. Direct/Indirect minimum individual unit length is 48".
- Minimum length is 96 1/8". Roll optic for run lengths will ship separately and need to be ordered as an additional line item.
- Luminance Reducing Optic is only available in 600 lm/ft, 500 lm/ft and 400 lm/ft packages.
- Tunable White and Zumtobel SPECTRUM fixtures must be 4' or over in length and can only be supplied in 1' increments, and are not available with Asymmetric Optics. Must be ordered with T driver option.
- Enlighted Control not available with wet or damp location rating.
- Only available with 0-10 V dimming.
- Add EM circuit option when designating only a portion of a continuous run is to be circuited for emergency. If an entire fixture or entire run is EM then this option is provided as standard.
- EM battery available in minimum 8' length with Direct/Indirect option. EM battery available in 4' length with Direct only or Indirect only options. EM is not available with 347V driver option. EM battery not available with wet location rating.

2.5" Pendant / Wall Mount Corner

LENS OPTIC OPTIONS

SLOTLIGHT LED III

2.5" Configurations with Corners

- Continuous line of light
- Available in a variety of lengths to suit any application
- Patented roll lens for seamless installation
- Rollable lens for all direct optics: opal flush / regressed (150' max length) and asymmetric (50' max length)
- Uniformly illuminated corners
- Available with occupancy and daylight sensors
- UGR <19 with LRO Lens

IBEW UNION MADE

Order Code



Suitable for Damp Locations

SL3C	2	3	4	5	6	7	8	9	10	9	12	13	14	15	16	17	18	19
1 FIXTURE	SL3C Configurations																	
2 WIDTH	2 2.5"																	
3 MOUNTING	PA Pendant, 70" feed PB Pendant 157" feed WM Wall Mount																	
4 WHOLE LENGTH	XXXX Length in 1" Increments																	
5 TYPE	L 1 Corner U 2 Corners R Rectangle S Square Z Custom																	
6 DISTRIBUTION	D Direct Only I Indirect Only C Single Channel Direct/Indirect S Separate Switching Direct/Indirect																	
7 DIRECT OUTPUT	09 900 lm/ft 08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
8 DIRECT OPTIC	P Opal Flush (Roll Optic) L Luminance Reducing ¹ A Asymmetric (Roll Optic) N None																	
9 INDIRECT OUTPUT	10 1000 lm/ft 09 900 lm/ft 08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
10 INDIRECT OPTIC	B Batwing A Asymmetric N None																	
11 CRI	9 90 CRI																	
12 CCT	30 3000 K 35 3500 K 40 4000 K 00 Tunable White 2700–6500 K ² ZS Zumtobel SPECTRUM ²																	
13 DRIVER	U 0-10 V, 1%, 120 V / 277 V D DALI, 1%, 120 V / 277 V H Lutron EcoSystem, 1%, 120 V / 277 V C 0-10 V, 1%, 347 V T Tunable White DALI Signal ²																	
14 FINISH	W White S Silver B Black																	
15 CONTROL OPTIONS	N None E Enlited ³ W Wireless ³																	
16 ACCESSORIES	C EM Circuit ⁴ B Battery ⁵																	
17 EM START	1 Start EM 0 None																	
18 EM MID	X Quantity from 1 to 9 0 None																	
19 EM END	1 End EM 0 None																	

1 Luminance Reducing Optic is only available with 600 lm/ft, 500 lm/ft or 400 lm/ft packages

2 Must consult factory for Tunable White or Zumtobel SPECTRUM configurations, are not available with Asymmetric Optics. Must be ordered with **T** driver option.

3 Only available with 0-10 V dimming. Enlited Control not available with wet or damp location rating.

4 Add EM circuit option when designating only a portion of a continuous run is to be circuited for emergency. If an entire fixture or entire run is EM then this option is provided as standard.

5 EM battery available in minimum 8' length with Direct/Indirect option. EM battery available in 4' length with Direct only or Indirect only options. EM is not available with 347V driver option.

Feed Canopy Suspension Kit Order Code

SUS	2	3	4	5	6
1 SUSPENSION	SUS Suspension Kit				
2 MOUNTING	070 70" Cable 157 157" Cable				
3 CANOPY TYPE	ST Standard DP Deep ¹ DE Deep Conduit End ¹ DL Deep Conduit 'L' ¹ DS Deep Conduit Straight ¹ DT Deep Conduit 'T' ¹				
4 CANOPY	1J5 Single Point J-Box 5" 1T5 Single Point T-Bar 5"				
5 FEED	SF Single Feed DF Dual Feed				
6 COLOR	B Black S Silver W White				

1 Only available on J5 without EM

Non-Feed Canopy Suspension Kit Order Code

SUS	2	ST	4	NF	6
1 SUSPENSION	SUS Suspension Kit				
2 MOUNTING	070 70" Cable 157 157" Cable				
3 CANOPY TYPE	ST Standard				
4 CANOPY	1S1 Single Point Structure 1" ¹ 1T2 Single Point T-Grid 2" ²				
5 FEED	NF No Feed				
6 COLOR	B Black S Silver W White				

1 Works with 1J5 Feed

2 Works with 1T5 Feed

Suspension kits must be ordered with and without Power Feeds. For example: an 8' individual pendant requires BOTH one suspension kit with a feed and one suspension kit without a feed.


SEE PAGE 5 FOR SUSPENSION KIT COMPONENT DETAILS.

Component Order Codes

The lens is a polycarbonate, field cuttable, roll lens shipped in various length rolls.

2.5" Width			
25' Roll Optic Opal Flush	M0048003-25	25' Roll Optic Luminance Reducing	05600202
50' Roll Optic Opal Flush	M0048003-50	25' Roll Optic Asymmetric	05600208
100' Roll Optic Opal Flush	M0048003-100	50' Roll Optic Luminance Reducing	05600203
150' Roll Optic Opal Flush	M0048003-150	50' Roll Optic Asymmetric	05600209
Lens Removal and Cutting Kit	11055252		
Lens Joiner Kit, White	11055255		
Lens Joiner Kit, Black	11055421		
Lens Joiner Kit, Titan	11055426		

Optical Performance




Lumens*

		DIRECT												INDIRECT									
		Opal					LRO			Asymmetric					Batwing					Asymmetric			
		400	500	600	700	800	400	500	600	400	500	600	700	800	400	500	600	700	800	400	500	600	700
3000 K	LM/W	85	84	83	82	80	69	68	67	94	93	92	90	95	103	102	101	100	98	66	65	64	62
	W/ft	4.7	6.0	7.2	8.6	10.0	5.8	7.4	9.0	4.3	5.4	6.6	7.8	8.4	3.9	4.9	6.0	7.0	8.1	6.1	7.7	9.4	11.2
3500 K	LM/W	87	86	85	84	83	71	70	69	96	95	94	93	97	106	108	103	102	101	68	67	65	64
	W/ft	4.6	5.8	7.1	8.4	9.7	5.6	7.2	8.8	4.2	5.3	6.4	7.6	8.2	3.8	4.6	5.8	6.8	7.9	5.9	7.5	9.2	10.9
4000 K	LM/W	88	87	86	85	83	72	71	69	103	102	101	99	98	107	106	105	103	102	68	67	66	65
	W/ft	4.5	5.7	7.0	8.3	9.6	5.6	7.1	8.7	3.9	4.9	6.0	7.0	8.1	3.7	4.7	5.7	6.8	7.8	5.8	7.4	9.1	10.8

* Exact programming levels available as a modification.

Dimensions



Technical Detail

1) Construction: The Luminaire consists of a painted aluminum housing and a choice of opal/clear polycarbonate roll optics with integrated continuous feed wiring.

2) Wattage & CCT: Fixture is available in lumen packages of 1000 lm/ft (indirect only), 900 lm/ft (direct only), 800 lm/ft, 700 lm/ft, 600 lm/ft, 500 lm/ft and 400 lm/ft. Wattage is determined by lumen package and CCT chosen. Available in 3000 K, 3500 K or 4000 K color temperatures with 90+ CRI. 3-Step MacAdam Ellipse.

3) Drivers: The unit is available with standard 120 V / 277 V 0-10 V dimming driver (1%), 347 V 0-10 V dimming driver (1%), Lutron LDE1 Hi-lume 1% digital EcoSystem with SoftOn/ FadeToBlack, or DALI dimming driver (1%). For non-dimming applications a 0-10 V driver will be provided: cap off the two control wires and connect the hot/neutral and ground as normal. Wireless dimming is only available with all 0-10 V driver options.

Tunable White fixtures have the option of DALI controlled dimming signal or Osram Dexas. If Osram Dexas is a requirement compatible control interfaces must be purchased directly from Osram. DALI dimming option uses protocol 8. Wireless dimming is available through eLdoLED BLE radio and controlled by 4remote BT app or Bluetooth switches.

4) Zumtobel SPECTRUM: Please use QR code for complete details.



5) Optic/Lens: The unit is available with an Opal Flush optic obtained from a polycarbonate roll optic that is available in 25', 50', 100' and 150' continuous rolls for seamless run effect. A joining kit with cover plate will be required every 150' for longer run lengths. Field cutting instructions are provided with the standard installation guide. A lens cutting tool kit is available to order as a separate accessory. Roll lens for LRO and asymmetric fixtures are available in 25' rolls, a joining kit with cover plate will be required every 25' for longer run lengths. If UGR <19 is a project requirement please order with LRO roll optic.

Asymmetric optic can be provided in either direction perpendicular to the length and will be designated 'right' or 'left' based on power feed in. The factory will consult client for desired asymmetric optic direction.

6) Mounting: Suspension Kits include high strength galvanized steel aircraft cable 70" or 157" in length. Suspensions spacing is 8 feet on center maximum. Wall mount bracket provided, 8 feet on center typical.

7) Length: Individual fixtures and straight runs lengths can be ordered in exact length increments of 1/8" with a 2' minimum. Lengths of 8' and under are provided as individual fixtures. Lengths greater than 8' are provided as runs comprising of start, middle and end sections.

Configurations total length should be measured from the outside perimeter of the configuration to the nearest foot, Shop drawings with the exact configuration measurements will be provided with all configuration orders for approval.

Individual units have pre-installed roll optic within the fixture, for runs and configurations the roll optic will be provided in a separate roll to be field installed and will appear as an additional line item on shipping documentation.

8) Controls: Fixtures can be purchased with Enlighted ready controls and daylight saving/ occupancy sensor, this option requires an Enlighted compatible control interface provided by others to function. All orders with a sensor chosen will be provided with drawings showing the exact sensor placement.

9) Emergency Options: Fixtures can be either purchased for emergency circuit or emergency battery operation. EM Battery fixtures are available as start, middle or end fixtures. The factory will consult with the client for EM placement on configurations. Average Lumen output for EM Battery is 600 Lumens.





10) Life: 50,000 hours, L85.

11) Weight: 4.45lbs per 2ft.

12) Declare Information:



Pendant Suspensions



We reserve the right to change, without notice, specifications or materials. Supporting documentation found on zumtobel.us are the most recent versions and supersede all other versions that exist in any other printed or electronic form.