

1.5" Pendant (shown) / Wall Mount

LOUVER OPTIC OPTIONS

SLOTLIGHT LED III

1.5" Individual Luminaires and Straight Runs

- Continuous line of light
- Available in a variety of lengths to suit any application
- Available with occupancy and daylight sensors
- UGR <19 with specific louver options

IBEW UNION MADE

PROGRAMMABLE LM/FT RANGES *

OPTIC	3000 K		3500 K		4000 K	
	MIN	MAX	MIN	MAX	MIN	MAX
Matte Black Louver	165	401	169	411	172	417
Gloss Black Louver	170	414	175	424	177	430
Silver Louver	268	650	275	666	279	677
White Louver	396	961	406	985	412	1000
Indirect Batwing	273	743	279	761	282	769
Indirect Asymmetric	74	402	76	412	76	416

* Exact programming levels available as a modification.



Suitable for Damp Locations

Order Code

1

1

3

4

5

6

7

8

9

9

11

12

13

14

15

16

17

18

- 1 FIXTURE **SL3I** Individual¹ | **SL3R** Run²
- 2 WIDTH **1** 1.5"
- 3 MOUNTING **PA** Pendant 70" Feed | **PB** Pendant 157" Feed | **WM** Wall Mount
- 4 WHOLE LENGTH **XXXXFT** Length in 1' Increments (minimum length is 4')
- 5 DISTRIBUTION **D** Direct Only | **I** Indirect Only | **C** Single Channel Direct/Indirect | **S** Separate Switching Direct/Indirect
- 6 DIRECT OUTPUT **08** 800 lm/ft | **07** 700 lm/ft | **06** 600 lm/ft | **05** 500 lm/ft | **04** 400 lm/ft | **00** No Output
- 7 DIRECT OPTIC **W** Matte White Louver³ | **G** Gloss Black Louver⁴ | **B** Matte Black Louver⁴ | **S** Matte Silver Louver⁵ | **N** None
- 8 INDIRECT OUTPUT **08** 800 lm/ft | **07** 700 lm/ft | **06** 600 lm/ft | **05** 500 lm/ft | **04** 400 lm/ft | **00** No Output
- 9 INDIRECT OPTIC **B** Batwing | **A** Asymmetric⁶ | **N** None
- 10 CRI **9** 90 CRI
- 11 CCT **30** 3000 K | **35** 3500 K | **40** 4000 K
- 12 DRIVER **U** 0-10 V, 1%, 120 V / 277 V | **D** DALI, 1%, 120 V / 277 V | **H** Lutron EcoSystem, 1%, 120 V / 277 V | **C** 0-10 V, 1%, 347 V
- 13 FINISH **W** White | **S** Silver | **B** Black
- 14 CONTROL OPTIONS **N** None | **E** Enlighted⁷ | **W** Wireless⁷
- 15 ACCESSORIES * **C** EM Circuit⁸ | **B** Battery⁹
- 16 EM START **1** Start EM | **0** None
- 17 EM MID **X** Quantity from 1 to 9 | **0** None
- 18 EM END **1** End EM | **0** None

* COMPLETE 15-18 IF EMERGENCY OPTIONS ARE REQUIRED

- 1 Must be between 2' and 8' in length. Direct/Indirect minimum individual unit length is 48".
- 2 Minimum length is 9'.
- 3 Matte White Louver is only available with 800 lm/ft, 700 lm/ft and 600 lm/ft packages.
- 4 Matte and Gloss Black Louvers are only available with 400 lm/ft package.
- 5 Matte Silver Louver is only available with 600 lm/ft, 500 lm/ft and 400 lm/ft packages.
- 6 Indirect Asymmetric lens is only available with 400 lm/ft package.
- 7 Only available with 0-10 V dimming. Enlighted Control not available with damp location rating.
- 8 Add EM circuit option when designating only a portion of a continuous run is to be circuited for emergency. If an entire run or entire fixture is EM then this option is provided as standard.
- 9 EM battery available in minimum 8' length with Direct/Indirect option. EM battery available in 4' length with Direct only or Indirect only options. EM is not available with 347 V driver option. EM battery not available with damp location rating.

We reserve the right to change, without notice, specifications or materials. Supporting documentation found on zumtobel.us are the most recent versions and supersede all other versions that exist in any other printed or electronic form.

LOUVER OPTIC OPTIONS

SLOTLIGHT LED III

1.5" Configurations with Corners

- Continuous line of light
- Available in a variety of lengths to suit any application
- Available with occupancy and daylight sensors
- UGR <19 with specific louver options

IBEW UNION MADE



Suitable for Damp Locations

Order Code

SL3C	1	3	4	5	6	7	8	9	10	9	12	13	14	15	16	17	18	19
1 FIXTURE	SL3C Configurations																	
2 WIDTH	11.5"																	
3 MOUNTING	PA Pendant 70" Feed PB Pendant 157" Feed WM Wall Mount																	
4 WHOLE LENGTH	XXXFT Length in 1' Increments																	
5 TYPE	L 1 Corner U 2 Corners R Rectangle S Square Z Custom																	
6 DISTRIBUTION	D Direct Only I Indirect Only C Single Channel Direct/Indirect S Separate Switching Direct/Indirect																	
7 DIRECT OUTPUT	08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
8 DIRECT OPTIC	W Matte White Louver ¹ G Gloss Black Louver ² B Matte Black Louver ² S Matte Silver Louver ³ N None																	
9 INDIRECT OUTPUT	08 800 lm/ft 07 700 lm/ft 06 600 lm/ft 05 500 lm/ft 04 400 lm/ft 00 No Output																	
10 INDIRECT OPTIC	B Batwing A Asymmetric ⁴ N None																	
11 CRI	9 90 CRI																	
12 CCT	30 3000 K 35 3500 K 40 4000 K																	
13 DRIVER	U 0-10 V, 1%, 120 V / 277 V D DALI, 1%, 120 V / 277 V H Lutron EcoSystem, 1%, 120 V / 277 V C 0-10 V, 1%, 347 V																	
14 FINISH	W White S Silver B Black																	
15 CONTROL OPTIONS	N None E Enlighted ⁵ W Wireless ⁵																	
16 ACCESSORIES *	C EM Circuit ⁶ B Battery ⁷																	
17 EM START	1 Start EM 0 None																	
18 EM MID	X Quantity from 1 to 9 0 None																	
19 EM END	1 End EM 0 None																	

* COMPLETE 16-17 IF EMERGENCY OPTIONS ARE REQUIRED

- Matte White Louver is only available with 800 lm/ft, 700 lm/ft and 600 lm/ft packages.
- Matte and Gloss Black Louvers are only available with 400 lm/ft package.
- Matte Silver Louver is only available with 600 lm/ft, 500 lm/ft and 400 lm/ft packages.
- Indirect Asymmetric lens is only available with 400 lm/ft package.
- Only available with 0-10 V dimming. Enlighted control option not available with damp location rating.
- Add EM circuit option when designating only a portion of a continuous run is to be circuited for emergency. If an entire run or entire fixture is EM then this option is provided as standard.
- EM battery available in minimum 8' length with Direct/Indirect option. EM battery available in 4' length with Direct only or Indirect only options. EM is not available with 347V driver option. EM battery not available with damp location rating.

Feed Canopy Suspension Kit Order Code

SUS	2	3	4	5	6
1 SUSPENSION	SUS Suspension Kit				
2 MOUNTING	070 70" Cable 157 157" Cable				
3 CANOPY TYPE	ST Standard DP Deep ¹ DE Deep Conduit End ¹ DL Deep Conduit 'L' ¹ DS Deep Conduit Straight ¹ DT Deep Conduit 'T' ¹				
4 CANOPY	1J5 Single Point J-Box 5" 1T5 Single Point T-Bar 5"				
5 FEED	SF Single Feed DF Dual Feed				
6 COLOR	B Black S Silver W White				

1 Only available on J5 without EM

Suspension kits must be ordered with and without Power Feeds. For example: an 8' individual pendant requires BOTH one suspension kit with a feed and one suspension kit without a feed.

SEE PAGE 5 FOR SUSPENSION KIT COMPONENT DETAILS.

Non-Feed Canopy Suspension Kit Order Code


SUS	2	ST	4	NF	6
1 SUSPENSION	SUS Suspension Kit				
2 MOUNTING	070 70" Cable 157 157" Cable				
3 CANOPY TYPE	ST Standard				
4 CANOPY	1S1 Single Point Structure 1" ¹ 1T2 Single Point T-Grid 2" ²				
5 FEED	NF No Feed				
6 COLOR	B Black S Silver W White				

1 Works with 1J5 Feed

2 Works with 1T5 Feed

We reserve the right to change, without notice, specifications or materials. Supporting documentation found on zumtobel.us are the most recent versions and supersede all other versions that exist in any other printed or electronic form.

Optical Performance




Lumens*

		DIRECT									INDIRECT				
		Matte White Louver				Matte Black Louver	Gloss Black Louver	Matte Silver Louver			Batwing				Asymmetric
		600	700	800	900	400	400	400	500	600	400	500	600	700	400
3000 K	LM/W	86	85	84	83	34	36	59	57	56	67	66	64	63	34
	W/ft	6.9	8.2	9.5	10.8	11.6	11.2	6.8	8.7	10.6	6.0	7.6	9.3	11.1	11.8
3500 K	LM/W	89	88	87	85	35	37	60	59	58	69	67	66	65	35
	W/ft	6.8	8.0	9.2	10.5	11.3	10.9	6.7	8.5	10.4	5.8	7.4	9.1	10.8	11.5
4000 K	LM/W	90	89	88	87	36	37	61	60	59	69	68	67	66	35
	W/ft	6.7	7.9	9.1	10.3	11.1	10.7	6.5	8.3	10.2	5.8	7.3	9.0	10.6	11.3

* Exact programming levels available as a modification.

We reserve the right to change, without notice, specifications or materials. Supporting documentation found on zumtobel.us are the most recent versions and supersede all other versions that exist in any other printed or electronic form.

Dimensions



Technical Detail

1) Construction: The Luminaire consists of a painted aluminum housing and a choice of louver options. Louvers available in Matte White, Gloss Black, Matte Black and Matte Silver.

2) Wattage & CCT: Fixture is available in lumen packages of 800 lm/ft, 700 lm/ft, 600 lm/ft, 500 lm/ft and 400 lm/ft. Wattage is determined by lumen package and CCT chosen. Available in 3000 K, 3500 K or 4000 K color temperatures with 90+ CRI. 3-Step MacAdam Ellipse.

3) Drivers: The unit is available with standard 120 V / 277 V 0-10 V dimming driver (1%), 347 V 0-10 V dimming driver (1%), Lutron LDE1 Hi-lume 1% digital EcoSystem with SoftOn/ FadeToBlack, or DALI dimming driver (1%). For non-dimming applications a 0-10 V driver will be provided: cap off the two control wires and connect the hot/neutral and ground as normal. Wireless dimming is only available with all 0-10 V driver options. Wireless dimming is available through eldoLED BLE radio and controlled by 4remote BT app or Bluetooth switches.

4) Optic/Lens: The unit is available with choice of injection molded louvers for visual comfort. If UGR <19 is a project requirement

please order the fixture with either black or silver louver options. White louvers do not meet the UGR <19 requirements. Asymmetric optic can be provided in either direction perpendicular to the length and will be designated 'right' or 'left' based on power feed in. The factory will consult client for desired asymmetric optic direction.

5) Mounting: Suspension Kits include high strength galvanized steel aircraft cable 70" or 157" in length. Suspensions spacing is 8 feet on center maximum. Wall mount bracket provided, 8 feet on center typical.

6) Length: Individual fixtures and straight runs lengths can be ordered in exact length increments of 1' with a 4' minimum. Lengths of 8' and under are provided as individual fixtures. Lengths greater than 8' are provided as runs comprising of start, middle and end sections.

Configurations total length should be measured from the outside perimeter of the configuration to the nearest foot, Shop drawings with the exact configuration measurements will be provided with all configuration orders for approval.

7) Controls: Fixtures can be purchased with Enlighted ready controls and daylight saving/ occupancy sensor, this option requires an Enlighted compatible control interface provided by others to function. All orders with a sensor chosen will be provided with drawings showing the exact sensor placement.

8) Emergency Options: Fixtures can be either purchased for emergency circuit or emergency battery operation. EM Battery fixtures are available as start, middle or end fixtures. The factory will consult with the client for EM placement on configurations. Average Lumen output for EM Battery is 600 Lumens.





9) Life: 50,000 hours, L85.

10) Weight: 4.45lbs per 2ft.

11) Declare Information:



Pendant Suspensions



We reserve the right to change, without notice, specifications or materials. Supporting documentation found on zumtobel.us are the most recent versions and supersede all other versions that exist in any other printed or electronic form.