

**ZUMTOBEL**

GLOBAL TRAC™

GLOBAL TRAC™ LUMINAIRE



Medium Trackhead

ONICO

Medium Trackhead for Global Trac™

- Passive cooling achieved by innovative thermal design
- Driver integrated into the housing
- Die-cast aluminum housing
- Rotatable head through 328° and tiltable through 90°
- Black polycarbonate front ring provides excellent glare control
- Front ring serves for accommodation of accessories
- Reflector of aluminized polycarbonate, highly specular, iridescence-free
- Specular reflector designed to be interchangeable



Suitable for Dry Locations

IBEW UNION MADE

DELIVERED LUMENS	COLOR TEMPERATURE	COLOR RENDERING	WATTS
1800 lm – 2358 lm	3000 K	CRI 80+	24 W
	3500 K	CRI 90+	
	4000 K		
	(MacAdam 3 Step)		

Trackhead Order Code

ONICM	24W	3	4	5	6	UNV
--------------	------------	----------	----------	----------	----------	------------

1	FIXTURE	ONICM Spotlight
2	OUTPUT	24W 1800 lm – 2358 lm
3	LED MODULE	830 3000K, 80CRI 835 3500K, 80CRI 840 4000K, 80CRI 930 3000K, 90CRI 935 3500K, 90CRI 940 4000K, 90CRI
4	BEAM SPREAD	SP Spot 11° FL Flood 25° WF Wide Flood 40°
5	FINISH	WH White BK Black
6	ADAPTER	TEK 2-Circuit, 120V HTEK 2-Circuit, 277V
7	DRIVER	UNV 120V/277V

Accessories Order Code



60700382	Interchangeable Spot Reflector	60700369	Soft Outline Lens
60700383	Interchangeable Flood Reflector	60700371	Oval Outline Lens
60700384	Interchangeable Wide Flood Reflector	60700373	Honeycomb Louver, Black

Track Order Code

Track elements must be ordered separately. Consult Global Trac™ specification sheets for order codes.

Light Distribution

Dimensions




Multipliers

CCT and CRI		
CRI	CCT	Multiplier
90	3000	1.00
	3500	1.07
	4000	1.08
80	3000	1.27
	3500	1.30
	4000	1.31

Illuminance at a Distance | 24 W, 90 CRI, 3000 K

11° Spot				25° Flood				40° Wide Flood			
Center Beam				Center Beam				Center Beam			
D	FC	L	W	D	FC	L	W	D	FC	L	W
5'	667	1.3'	1.3'	5'	322	2.0'	2.0'	5'	166	3.0'	3.0'
7.5'	296	1.8'	1.8'	7.5'	143	3.1'	3.1'	7.5'	74	4.6'	4.6'
10'	166	2.5'	2.5'	10'	80	4.2'	4.2'	10'	42	6.0'	6.0'
12.5'	106	3.1'	3.1'	12.5'	51	5.2'	5.2'	12.5'	26	7.8'	7.8'
15'	74	3.7'	3.7'	15'	35	6.3'	6.3'	15'	18	9.2'	9.2'



CBCP: 16689 | Lumens: 1800
LPW: 75 lm/W

CBCP: 8064 | Lumens: 1800
LPW: 75 lm/W

CBCP: 4168 | Lumens: 1800
LPW: 75 lm/W

Technical Detail

- 1) Track:** ONICO is compatible with Global Trac™.

2) Wattage & CCT: Unit is available in 24 W, 3000 K, 3500 K, 4000 K and in 80+ and 90+ CRI.

3) Dimming: Unit is only available with a non-dimmable universal 120/277V driver.
- 4) Beam Spread:** Unit is available with Spot, Flood or Wide Flood beam spread.

5) Accessories: Honeycomb louver (black), oval outline lens, soft outline lens and interchangeable reflectors (Spot, Flood and Wide Flood distribution) are offered as accessories.

6) Housing: The housing is made of diecast aluminum painted white.
- 7) Optic:** The reflector is polycarbonate (PC) aluminum sputtered specular.

8) Life: 50,000 hours, L80.

9) Weight: 2.0 lbs.